



Sea Foam Sales Company
510 North Chestnut Street
Chaska, MN, USA 55318

Sea Foam Motor Treatment
SDS Revision Date: 10/16/2019

SAFETY DATA SHEET

Applicable Law: USA
Page 1 of 7

SECTION 1. IDENTIFICATION

Product identifier used on the label : Sea Foam Motor Treatment

Product Code(s) : SF-16, SF-20, SF-128, SF-55, ST-20

Recommended use of the chemical and restrictions on use : Fuel system treatment
Use pattern: Consumer use; professional use.

Chemical family : Mixture.

Name, address, and telephone number of the supplier : Sea Foam Sales Company
510 North Chestnut Street
Chaska, MN, USA 55318
T (952) 938-4811

Name, address, and telephone number of the manufacturer : Refer to supplier

Emergency Telephone Number : INFOTRAC - (800) 535-5053 (Within Continental US) (8-4:30pm CST);
+1 (352) 323-3500 (Outside US) NOTE: INFOTRAC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.



SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture
Clear liquid. Petroleum hydrocarbon odor

GHS US classification

Flammable liquid - Category 2
Serious eye damage/eye irritation - Category 2A
Specific target organ toxicity - single exposure - Category 3
Aspiration toxicity - Category 1

GHS Label elements, including precautionary statements

Hazard pictograms (GHS US)



Signal Word

DANGER

Hazard statement(s)

Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause drowsiness and dizziness.
May be fatal if swallowed and enters airways.

Precautionary statement(s)

Keep away from heat, sparks and open flame. - No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/clothing and eye/face protection.
Wash hands and face thoroughly after handling.
Avoid breathing vapor or mist.
Use only outdoors or in a well-ventilated area.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam for extinction.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local regulation.

Other Hazards which do not result in classification

Burning produces noxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin.



SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS #</u>	<u>Concentration</u>
Hydrocarbon blend*	Blend	< 95%
Isopropanol	67-63-0	< 25%

*Note: The exact composition of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

<i>Ingestion</i>	: Seek immediate medical attention/advice. Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
<i>Inhalation</i>	: Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.
<i>Skin contact</i>	: Immediately remove/take off all contaminated clothing. Wash exposed area thoroughly with soap and water for at least 15 minutes. If irritation or symptoms develop, seek medical attention.
<i>Eye contact</i>	: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Most important symptoms and effects, both acute and delayed

: Causes serious eye irritation.
Causes respiratory tract irritation.
May cause drowsiness and dizziness.
May cause damage to the nervous system through prolonged or repeated exposure.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. This product is a CNS depressant.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media : Dry chemical, foam, carbon dioxide and water fog.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

: Highly flammable liquid and vapor. May be ignited by open flame. Vapors are heavier than air and collect in confined and low-lying areas. The product is insoluble and floats on water. The pressure in sealed containers can increase under the influence of heat.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable liquid - Category 2

Explosion Data: Sensitivity to Mechanical Impact / Static Discharge

: Not expected to be sensitive to mechanical impact. May be sensitive to static discharge. Vapors in the flammable range may be ignited by a static discharge of sufficient energy.

Hazardous combustion products

: Carbon oxides; Nitrogen oxides (NOx); Sulphur oxides; Other unidentified organic compounds; irritating fumes and smoke.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece, operated in positive pressure mode.

Special fire-fighting procedures : Move containers from fire area, if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Direct water or foam spray may cause frothing which can increase the intensity and range of the fire.



SAFETY DATA SHEET

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. Soak up with inert absorbent material. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).

US CERCLA Reportable quantity (RQ): None.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye/face protection. Use only in well-ventilated areas. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and open flame. - No smoking.

Ground/Bond container and receiving equipment. Take precautionary measures against static discharges. Use explosion-proof ventilating equipment. Keep container tightly closed. Do not eat, drink or smoke when using this product. Empty containers retain residue (liquid and/or vapor) and can be dangerous. Wash thoroughly after handling.

Conditions for safe storage

: Store in a cool, dry, well-ventilated area. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. No smoking. Protect from sunlight. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Hydrocarbon blend	5 mg/m ³ (inhalable fraction, mineral oil mists)	N/Av	5 mg/m ³ (As 'Oil mist, mineral')	N/Av
Isopropanol	200 ppm	400 ppm	400 ppm ; 980 mg/m ³	N/Av

Exposure controls

Ventilation and engineering measures

: Provide mechanical ventilation in confined spaces. Use explosion-proof equipment.

Respiratory protection

: If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised.

Skin protection

: Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers. Wear long sleeved shirt and pants to minimize exposed skin.

Eye / face protection

: Chemical safety glasses with side shields or splash proof goggles. A full-face shield may also be necessary.

Other protective equipment

: Depending on conditions of use, an impervious apron should be worn. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.



SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear liquid.

Odor:

Typical odor.

Odor threshold:

No information available.

pH:

No information available.

Melting/Freezing point:

No information available.

Initial boiling point and boiling range:

No information available.

Flash point:

12.8°C / 55°F

Flashpoint (Method):

TCC

Evaporation rate (BuAe = 1):

<1

Flammability (solid, gas):

Not applicable.

Lower flammable limit (% by vol.):

No information available.

Upper flammable limit (% by vol.):

No information available.

Oxidizing properties:

None known.

Explosive properties:

Not explosive.

Vapor pressure:

No information available.

Vapor density:

>1

Relative density / Specific gravity:

0.819

Solubility in water:

Insoluble.

Other solubility(ies):

No information available.

Partition coefficient n-octanol/water:

No information available.

Auto-ignition temperature:

No information available.

Decomposition temperature:

No information available.

Viscosity:

No information available.

Volatiles (% by weight):

No information available.

Volatile organic Compounds (VOC's):

367g/l

Absolute pressure of container:

Not applicable.

Flame projection length:

Not applicable.

Other physical/chemical comments:

No addition information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Not normally reactive.

Chemical stability

: Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerisation does not occur.

Conditions to avoid

: Avoid heat and open flame. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials.

Incompatible materials

: Strong oxidizing agents; Acids; Caustics.

Hazardous decomposition products

: None known. Refer to hazardous combustion products in Section 5.



SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation: YES

Routes of entry skin and eye: YES

Routes of entry ingestion: YES

Routes of exposure skin absorption: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms inhalation

: Inhalation of vapors can cause nasal and respiratory irritation. Exposure to high vapor concentration can cause dizziness, nausea and central nervous system depression. Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation.

Sign and symptoms ingestion

: Swallowing may cause irritation, nausea and vomiting. May cause central nervous system depression. May be absorbed and cause symptoms similar to those for inhalation. Symptoms may include burning pain, vomiting and diarrhea. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Sign and symptoms skin

: May cause mild skin irritation. May be absorbed and cause symptoms similar to those for inhalation.

Sign and symptoms eyes

: May cause moderate eye irritation.

Potential chronic health effects

: Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin. Prolonged overexposure to product can result in permanent central nervous system changes. May cause lung inflammation and lung damage with extreme exposures.

Mutagenicity

: Not expected to be mutagenic in humans.

Carcinogenicity

: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects and teratogenicity

: Not expected to have other reproductive effects.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

: Eyes, skin, respiratory system, digestive system, central nervous system. The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects. The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Irritancy

: Moderate eye irritant. Irritating to respiratory system. Mild skin irritant.

Medical conditions aggravated by overexposure : None known or reported by the manufacturer.

Synergistic materials

: None known or reported by the manufacturer.

Toxicological data

: The calculated ATE values for this mixture are:
ATE oral = 23,600 mg/kg
ATE dermal = 8,343 mg/kg
ATE inhalation (mists) = 65.7 mg/L/4H

See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC₅₀ (4 hr)</u> <u>inh, rat</u>	<u>(Oral, rat)</u>	<u>LD₅₀</u> <u>(Rabbit, dermal)</u>
Hydrocarbon Blend	N/Av	>15000 mg/kg	>5000 mg/kg
Isopropanol	17000 ppm	4720 mg/kg	12890mg/kg

Other important toxicological hazards : None known or reported by the manufacturer.



SAFETY DATA SHEET

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity	: No data is available on the product itself
Persistence and degradability	: The product itself has not been tested. Contains: Isopropanol. Isopropanol is considered to be readily biodegradable.
Bioaccumulation potential	: The product itself has not been tested.
Mobility in soil	: The product itself has not been tested.
Other adverse environmental effects	: None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for disposal	: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not cut, weld, drill or grind on or near this container.
Methods of disposal	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Empty containers or liners may retain some product residues.
RCRA	: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (Contains Petroleum Distillates; Isopropanol)	3	II	
49CFR/DOT Additional information	ERG #128 The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment, or other regulatory descriptors. The packaging exceptions contained in 49 C.F.R. § 173.150 apply.				

Special precautions for user	: Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.
------------------------------	--

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	: This information is not available.
--	--------------------------------------

SECTION 15. REGULATORY INFORMATION

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

US CERCLA Reportable quantity (RQ): None.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: Isopropanol.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

Other U.S. State "Right to Know" Lists: The following chemicals are specifically listed by individual States: Isopropanol (MA, MN, NJ, CA, PA, RI)



Sea Foam Sales Company
510 North Chestnut Street
Chaska, MN, USA 55318

Sea Foam Motor Treatment
SDS Revision Date: 10/16/2019

SAFETY DATA SHEET

Applicable Law: USA
Page 7 of 7

SECTION 16. OTHER INFORMATION

NFPA Ratings:



Disclaimer: Sea Foam Sales Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.